


LAMP PHOTOMETRIC REPORT

MODEL: 99POM1505040/BL		
POWER: 50W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 4823.0 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	1886	1899	1905	1897	1894	1898	1907	1901	0- 10	183.6	183.6	3.81
20	1722	1759	1788	1756	1740	1758	1788	1764	10- 20	518.3	701.8	14.6
30	1478	1543	1598	1538	1500	1541	1598	1549	20- 30	763.8	1466	30.4
40	1186	1274	1352	1268	1209	1271	1354	1282	30- 40	883.5	2349	48.7
50	885.8	975.7	1072	970.9	908.6	972.5	1075	984.7	40- 50	870.8	3220	66.8
60	595.1	676.1	775.8	672.0	613.7	673.8	781.7	685.0	50- 60	744.1	3964	82.2
70	317.6	386.2	480.8	383.3	334.2	384.3	486.0	394.2	60- 70	532.3	4496	93.2
80	75.06	125.6	209.2	124.1	88.09	124.2	213.3	132.0	70- 80	275.6	4772	98.9
90	1.895	2.369	3.212	2.461	1.559	2.101	2.917	2.060	80- 90	51.04	4823	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:01 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```